

CEYAKRETE

SUPREME QUALITY CONSTRUCTION CHEMICALS



Tile Adhesive

TA-P1

CeyaKrete Tile Adhesive is a cement based, polymer modified tile adhesive suitable for fixing a variety of ceramic tiles, mosaics, quarries, natural stone, marble and terrazzo in interior and exterior situations. CeyaKrete Tile Adhesive is suitable for walls and floors.

INSTRUCTIONS FOR USE

Surface Preparation:

Before starting any work, make sure that the base is sufficiently flat to permit the specified flatness of finished tiling.

The entire surface should be clean, dry, fully cured and free from all dirt, grease, oils, waxes, curing agents and any other surface contaminants.

MIXING AND APPLICATION

Add the adhesive powder to clean water. Mix until a smooth slump-free consistency is produced. Approximately 4-5 litres of water will be required for 20kg of CeyaKrete Tile Adhesive.

- Dampen the surface prior to application.
- Press tiles firmly into position and make sure that all the tiles are well bedded with no voids in the adhesive.
- Do not allow the adhesive to dry prior to tiling.

Grouting should be carried out at least 24 hours after completion of tiling.

CeyaKrete Tile Adhesive Liquid (TA-LQ1)

Tile over Tile - CeyaKrete Tile Adhesive mixed with TA-LQ1 can be used for installation of tiles over pre-installed tiles. This would reduce the time and costs of removing the old tiles and would also eliminate the need to redo the surface prior to the installation of tiles.

- The existing tiles should be soundly bonded to the surface.
- Thoroughly wash the existing tiles to remove contaminants.
- For glazed tiles, use a cup grinder to take the glaze off.

Mix 1 pack of 4.5kg **TA-LQ1** to 20kg of **TA-P1** instead of water.

PACKING: 20kg bags



ceyalac (Pvt) Ltd.

Ingiriya Road, Arukwatte,
Padukka, Sri Lanka.

Tel: +94 11 7222252

Fax: +94 11 2833602

Email:

ceyalac@crigroup.net

Sales Hotline:

773 83 39 29



www.ceyalac.com