

CEYAKRETE

construction chemicals & coatings

Manufactured by an
ISO 9001 2015
Certified Company

SKIM COAT

DESCRIPTION

Ceyakrete Skim Coat is a pre-packed premium quality cementitious fine finishing, filling and leveling water based compound manufactured by internationally accepted raw material and in compliance to international standards. The product is environmental and user-friendly and also gives a high quality, even surface for painting. When dry, the Skim Coat bonds extremely well to cementitious materials, gypsum, building boards, and all common masonry surfaces.

Can be used for patching hairline cracks and repairing damage to plaster or paint work. It can be used immediately by adding water.



SKIM COAT
ECO



SKIM COAT
PLUS+





SKIM COAT
PREMIUM+

FEATURES



Very Economical	■	■	■
Fine Particles for Excellent Finish	■	■	■
No Cracking & Peeling	■	■	■
Easy Sanding	■	■	■
High Workability	■	■	■
No Lime Ash	■	■	■
Interior & Exterior Use		■	■
Non Shrinking		■	■
Sanding Not Required for Finishing		■	■
High Polymer			■
Extremely Low Water Absorption			■
Suitable for Exterior Use			■
Ideal for Column and Soffit Applications			■



SPECIFICATIONS

COVERAGE: 100 – 120 Sq.Ft - 2 Coats
(Depending on the surface condition)

APPLICATION THICKNESS: 2 - 3 MM

WATER DEMAND: 6 - 6.5 Liters

PACK SIZE: 20KG

COLOUR: White / Gray

DRYING TIME: 4 - 5 Hours

POT LIFE: 4 Hours form the time of mixing.

SHELF LIFE: Up to 6 months in unopened bags and stored in a cool dry elevated position.

CERTIFICATION: ISO 9001:2015 Quality Management System and Certified Test Reports.

HEALTH & SAFETY: It is recommended to use protective gloves, goggles and clothing during handling. If skin irritation occurs, seek medical attention promptly.

INTRUCTIONS FOR USE

SURFACE PREPARATION

Ensure that all dust, dirt and foreign matter is scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges.

Before applying to old surfaces, ensure the substrate is firm. First wash down the surface and allow drying before repairing or applying the primer.

Surfaces to be treated should be thoroughly dampened with water.

MIXING AND APPLICATION

Mix 20Kg Skim Coat with 6 – 6.5 Liters clean potable water.

Mix for at least 3 - 5 minutes until a consistent and homogeneous lump-free mixture is obtained.

Apply Skim Coat on to moist, clean substrate using a flat-edge steel trowel. Apply the filler in a thin even layer (2mm - 3mm).

To increase thickness, a second coat can be applied just before the first coat is about to set. Lightly sand the final surface before painting. after completion of tiling.

DISCLAIMER: The use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specifications are subject to change without prior notice.

Member of



Group
ESTB 1950

Subsidiary of Ceylon Rubber Industries Ltd.



Ceyalac (Pvt) Ltd.

#10 (1st Floor), School Lane,
Colombo 03, Sri Lanka.

+94 11 7222252

+94 11 2507770

info@ceyalac.com

www.ceyalac.com

Sales Hotline: 773 833 929